



Key Functions

- Auto Exposure, Auto White Balance, Backlight Compensation
- Triple Stream (H.264, MJPEG) for simultaneous access to lo and hi resolution
- Onvif Profile S for compatibility with existing NVRs or PC or Mac software
- Easy Installation with IP Discovery software for Windows or Bonjour for Mac
- Full support for Internet Explorer, partial support for other browsers
- Advanced Intelligent Health Management automated diagnostic notification
- Event Boosting, FTP Image Upload, Open VPN, QoS, IP Filtering
- Privacy Masking with Face Detection
- Event Buffering for showing video prior to motion detection or other event

Similar Models in this series

- **HTNC4410LPC** (HTNC4410M special version for license plate capture at night)
- **HTNC4503M, HTNC4503DM** (5 Megapixel, 3x zoom IR bullet or dome camera)
- **HTNC4403DM** (IR dome, 3 x zoom)
- **HTNC4420PTZ** (PTZ dome, 20 x zoom)
- **HTNC4430XIR** (IR PTZ, 30 x zoom, extended IR 1300 ft night vision)


Software

- Includes free Titanium V2 256 camera viewing software for PC and Mac (requires MicroSD or Sharx Security NVR for recording, NVR recommended)
- Supports Milestone VMS (free for 8 cameras, any resolution, no time limit)
- Supports 16 Camera Blueiris on PCs, 16 camera SecuritySpy on Mac
- Supports Luxriot, Genetec, Aimetis, SightHound, OpenALPR, IPTimeLapse, VLC

Optional Sharx Accessories

- **HJB** Outdoor junction box with concealed cabling, suitable for pre-wiring
- **HCB** Outdoor conduit box, round, can be used with pole mount **HCPM**
- **HCPM** Heavy duty corner mount / pole mount, requires **HCB** conduit box
- **HTCP2701:** PoE power + networking for up to 1.5 miles range over coax
- **HTNR16560:** 480 fps 16-camera 5 MP NVR with 16 PoE, up to 24 TB storage
- **HTNR32620:** 960 fps 32-camera 4K NVR with 16 PoE, up to 48 TB storage
- **HTVM64600:** 1920 fps 64-camera 2/4/8 NVR link, up to 48 TB offsite storage
- **HTVM80600S:** 3840 fps 128-camera 2/4/8 NVR link, up to 96 TB offsite storage

Dimensions



Sharx HTNC4410M

Full HD 60 fps Outdoor Day/Night Camera, Motorized 10x Zoom

Key Features

- **Full HD(1920x1080) 60fps** for capturing fast motion or 30fps for higher light sensitivity
- **Motorized Vari-Focal 5.1 to 51mm, motorized 10 x optical zoom with auto focus**
- **True Wide Dynamic Range (120dB), True Day & Night**
- **32 IR LEDs for 75 ft Night Vision Coverage in total darkness**
- **Connectors for Audio In/Out (1/1), Alarm In/Out (1/1)**
- **Solid metal construction, cable connection concealed in camera mount**
- **Mounts to wall, eave or ceiling with or without optional junction box HJB**
- **MicroSDHC card up to 256 GB (optionally available from Sharx Security)**
- **Powered by PoE+ (802.3at) or 12VDC (power supply not included)**
- **Suitable for US government applications - made in Korea without Huawei components**

Technical Specifications

Model		Sharx Security HTNC4410M - made in South Korea	
IMAGE			
Lens		Motorized Vari-Focal Zoom 5.1 to 51.0 mm, built in Auto IRIS	
Angle of View		54° (standard perspective) to 4.9° (telephoto), horizontal measurement	
Image Sensor	Type	1/2.8" SONY Starvis CMOS Sensor	
	Pixels	1945 (H) x 1097 (V)	
Min. Illumination		Color : 0.35Lux / BW : 0 Lux, 50 IRE (IR LED On)	
Scanning Mode		Progressive Scan	
Wide Dynamic Range		True WDR(120dB)	
Day and Night Mode		True Day & Night (Auto, Day, Night)	
Noise Reduction		3DNR	
Digital Zoom		16X	
Exposure Control		Auto, Manual, Shutter Priority, Iris Priority	
White Balance Control		Auto, Incandescent, Fluorescent, Outdoor	
Back Light Compensation		Yes	
Image Effect		Flip (upside down)	
Flicker Free Mode		50Hz, 60Hz	
Shutter Speed		Auto (1/30,000 to 1/3 sec), Manual	
IR Illuminator	Quantity	32 IR LEDs, adjustable strength	
	Angle	78°	
	Distance	Up to 75 ft (25m) IR night vision in total darkness	
Minimum Focus Distance		0.3 ft (zoomed out) - 3 ft (zoomed in)	
VIDEO/AUDIO			
Compression		H.264 (Baseline, Main, High Profile), MJPEG	
Bitrate Control		CVBR, VBR	
Resolution		1920x1080, 1280x720/960/1024, 1024x768, 704x480/576, 640x360/480, 320x240	
Frame Rate		Max. 60fps @ Full-HD	
Streaming		60fps (Dual Stream : H.264x1, MJPEGx1), 30fps (Triple Stream : H.264x2, MJPEGx1)	
Composite Out		Yes (requires special cable accessory, not included)	
Audio Compression		AAC or G.711 (with user supplied external amplified microphone)	
Audio Streaming		2 Way (with user supplied external amplified speaker)	
SYSTEM			
Video Contents Analysis		Image Stabilization, Face Detection, Tampering, Line & Field Detector	
Motion Detection Area		16 Programmable Areas (8 Include Areas, 8 Exclude Areas)	
Special Features		Aisle mode (90 or 270 degree rotation), 8 Privacy Zones	
Email Attachment or FTP Upload		JPEG	
Event Notification		E-mail, FTP, Notification Server, XML Notification, Audio Alert, AIHM	
Audio Alert		User-Defined 3 Audio Files	
Login Authority		Administrator, Operator (with lens control), Guest	
Event Buffering	FTP	Pre : 30sec, Post : 30sec	
	SD Record	Pre : 10sec, Post : 60sec	
Manual Trigger		4 Programmable Triggers	
Security		Multi User Authority, IP Filtering, HTTPS & SSL (for admin/settings)	
Network Time Sync		NTP Server, Synchronized Computer, Manual	
Software Reset		Restart, Reset, Factory Default	
Hardware Factory Reset		Yes	
Auto Recovery		Backup, Restore	
Remote Upgrade		Yes	
SD Recording Mode		Event, Continuous	
NETWORK			
Protocol		TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour	
Client Software compatibility		Internet Explorer, Titanium, Milestone, LuxRiot, Blueiris, SecuritySpy, VLC	
Max. User Connection		Live : up to10 Users, Playback : up to3 Users	
API Support		Open API, Onvif Compliance	
Mobile Support		Mobilinc, tinyCam, ONVIF compatible apps, free Titanium for use with NVR	
EXTERNAL IN/OUT			
Video Composite Out		3.5mm jack for optional accessory monitor	
Audio		1 Input, 1 Output(3.5mm Stereo Jack)	
Alarm		1 Input, 1 Output(Terminal Block)	
Ethernet		RJ-45(10/100Base-T)	
MicroSD Card		MicroSDHC, MicroSDXC (Max 256GB, class 10 or faster)	
OSD Remote Control		Wired Remote Controller(3.5mm Stereo Jack, Optional)	
ETC			
Operating Humidity		0 to 100 % RH (Weatherproof in rain, snow, ice conditions)	
Operating Temperature		-22 to +120 degrees F (-30 to +50 °C)	
Power Supply (not included)		PoE+ (802.3 at Compliance) or 12VDC	
Power Consumption		Less than 15 watts when heater is not active (typically above 45 degrees F) 470mA (23W) @ PoE or 2.5A(30W) @ 12VDC when built in heater is active	
Dimensions		3.9" (Width) x 4.9" (Height) x 9.75" (Depth)	
Net Weight		2.3 lbs (1.04 kg)	
Ingress Protection		IP66	



www.sharxsecurity.com
info@sharxsecurity.com

Copyright © 2019 Sharx Security, Inc. All rights reserved.

Specifications are subject to change without notice.