



# Sharx HTNC4420PTZ

Full HD 60 fps Indoor/Outdoor Day/Night PTZ Dome, 20x Zoom

## Key Features

- Full HD (1920x1080) 60 fps for capturing fast motion or 30 fps for higher light sensitivity
- Motorized Vari-Focal 4.7 to 94 mm, full PTZ motorized 20 x optical zoom with auto focus
- True Wide Dynamic Range (120 dB)
- True Day & Night mode (use external IR illuminator for night vision in total darkness)
- 360 degrees endless pan / rotation, 100 degrees tilt range
- 380 degrees per second pan or tilt speed with presets
- 256 preset PTZ settings including tours, scans, privacy and motion presets
- Connectors for Audio In/Out (1/1), Alarm In/Out (1/1)
- Solid metal base with concealed cable connection on ceiling or with optional wall bracket
- MicroSDHC Card up to 256 GB (optionally available from Sharx Security)
- PoE, 12VDC, or 24V AC (power supply not included)
- Suitable for US government applications - made in Korea without Huawei components

## Technical Specifications

Model		Sharx Security HTNC4420PTZ - made in South Korea
<b>IMAGE</b>		
Lens	Optical Zoom 20X, 4.7~94mm	
Angle of View	55.5° (standard perspective) to 3° (super telephoto), horizontal measurement	
Image Sensor	Type	1/2.8" SONY STARVIS CMOS Sensor
	Pixels	1945(H)x1097(V)
Min. Illumination	Color : 0.35Lux, BW : 0.013Lux@50IRE	
Scanning Mode	Progressive Scan	
Wide Dynamic Range	True WDR (120dB)	
Day and Night Mode	True Day & Night	
Noise Reduction	3DNR	
Digital Zoom	16X	
Exposure Control	Auto, Manual, Shutter Priority, Iris Priority	
White Balance Control	Auto, Fluorescent, Incandescent, Outdoor, Manual	
Back Light Compensation	Yes	
Image Effect	Flip	
Shutter Speed	30fps : Auto(1/30,000 to 1/3 sec), Manual	
	60fps : Auto(1/50,000 to 1/3 sec), Manual	
<b>VIDEO/AUDIO</b>		
Compression	H.264(Baseline, Main, High Profile), MJPEG	
Bitrate Control	CVBR, VBR	
Resolution	1920x1080, 1280x1024, 1280x720/960, 704x480/576, 640x360/480, 320x240	
Frame Rate	Max. 60fps	
Streaming	60 fps(Dual Stream : H.264x1, MJPEGx1)	
	30 fps(Triple Stream : H.264x2, MJPEGx1)	
Audio Compression	AAC or G.711 (with user supplied external amplified microphone)	
Audio Streaming	2 Way (with user supplied external amplified speaker)	
<b>PTZ FUNCTION</b>		
Pan Range	360° Endless	
Pan Speed	Max. 380°/sec.(Presets)	
Tilt Range	-10°~190°	
Tilt Speed	Max. 380°/sec.(Presets)	
Auto Calibration	0.1~6"	
Preset	256	
Tour	8	
Pattern	8	
Home Function	Yes	
<b>SYSTEM</b>		
Video Contents Analysis	Image Stabilization, Face Detection, Tamper, Line & Field Detection	
Motion Detection Area	16 Programmable Areas (8 Include Areas, 8 Exclude Areas)	
Privacy Masking	16 Programmable Zones	
Email Attachment and FTP Upload	JPEG	
Event Notification	E-mail, FTP, Notification Server, XML Notification, Audio Alert, AIHM	
Audio Alert	User-Defined 3 Audio Files	
Login Authority	Administrator, Operator, Guest	
Event Buffering	FTP	Pre : 30sec, Post : 30sec
	SD Record	Pre : 10sec, Post : 60sec
Manual Trigger	4 Programmable Trigger	
Security	Multi User Authority, IP Filtering, HTTPS & SSL (for admin/settings)	
Network Time Sync	NTP Server, Synchronized Computer, Manual	
Software Reset	Restart, Reset, Factory Default	
Hardware Factory Reset	Yes	
Auto Recovery	Backup, Restore	
Remote Upgrade	Yes	
SD Recording Mode	Event, Continuous	
<b>NETWORK</b>		
Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour	
Client Software	Internet Explorer, Titanium, Milestone, LuxRiot, Blueiris, SecuritySpy, VLC	
Max. User Connection	Live : 10 Users, Playback : 3 Users	
API Support	Open API, Onvif Compliance	
Mobile Support	Mobilinc, tinyCam, ONVIF compatible apps, free Titanium for use with NVR	
<b>EXTERNAL IN/OUT</b>		
Audio	1 Input, 1 Output(3.5mm Stereo Jack)	
Alarm	4 Inputs, 1 Output	
Ethernet	RJ-45(10/100Base-T)	
u-SD Card	MicroSDHC, MicroSDXC (Max 256GB, class 10 or faster)	
<b>ETC</b>		
Operating Humidity	0 to 100% RH (Weatherproof in rain, snow, ice conditions)	
Operating Temperature	-22 F to +122 F powered by 24VAC, +14 F to +122 F powered by PoE or 12 V	
Power Supply	PoE (802.3af compliance), 12VDC, 24V AC	
Power Consumption	250mA(12W) @ PoE	
	1,000mA(12W) @ 12VDC, 1500mA(22W) @ 24V AC	
Dimension	6" diameter x 6" height (154 mm x 154 mm)	
Net Weight	Approx. 3.5 lbs (1.6kg)	
Ingress Protection	IP66	

## Key Functions

- Auto Exposure, Auto White Balance, Backlight Compensation
- Triple Stream (H.264, MJPEG) for simultaneous access to lo and hi resolution
- Onvif Profile S for compatibility with existing NVRs or software
- Easy Installation with IP Discovery software for Windows or Bonjour for Mac
- Full support for Internet Explorer, partial support for other browsers
- Advanced Intelligent Health Management automated diagnostic notification
- Event Boosting, FTP Image Upload, Open VPN, QoS, IP Filtering
- Privacy Masking with Face Detection
- Event Buffering for showing video prior to motion detection or other event

## Similar Models in this series

- **HTNC4410M** (10 x motorized zoom, bullet style camera)
- **HTNC4503M, HTNC4503DM** (5 MP, 3 x motorized zoom, bullet or dome)
- **HTNC4403DM** (IR dome, 3 x zoom)
- **HTNC4430XIR** (IR PTZ, 30 x zoom, extended IR 1300 ft night vision)


## Software

- Includes free Titanium V2 256 camera viewing software for PC and Mac (requires MicroSD or Sharx Security NVR for recording, NVR recommended)
- Supports Milestone VMS (free for 8 cameras, any resolution, no time limit)
- Supports 16 Camera Blueiris on PCs, 16 camera SecuritySpy on Mac
- Supports Luxriot, Genetec, Aimetis, SightHound, OpenALPR, IPTimeLapse, VLC

## Optional Sharx Accessories

- **HDB** Outdoor Wall Bracket with concealed cabling, suitable for pre-wiring
- **HCS** Indoor Flush Mount Ceiling Support Bracket, suitable for pre-wiring
- **HTCP2701**: PoE power + networking for up to 1.5 miles range over coax
- **HTNR16560**: 480 fps 16-camera 5 MP NVR with 16 PoE, up to 24 TB storage
- **HTNR32620**: 960 fps 32-camera 4K NVR with 16 PoE, up to 48 TB storage
- **HTVM64600**: 1920 fps 64-camera 2/4/8 NVR link, up to 48 TB offsite storage
- **HTVM80600S**: 3840 fps 128-camera 2/4/8 NVR link, up to 96 TB offsite storage

## Dimensions



www.sharxsecurity.com  
 info@sharxsecurity.com  
 Copyright © 2019 Sharx Security, Inc. All rights reserved.  
 Specifications are subject to change without notice.